

BED FEATURES

- Tamperproof fasteners
- 4 DC actuators
- Battery back-up
- 4 casters with central brake
- One hand release siderails
- One step Trendelenburg
- 4 corner roller bumpers
- Nurse controls integrated into siderails and footboard
- Patient controls integrated into siderails
- Motion control master lockout
- Profile deck regression
- Backrest angle indicator
- Reduced Ligature Attachment Point Configuration
- Floor Mounted fixation
- Fixed head & foot board
- Short power cord
- Detachable power cord
- Accessory socket caps
- Siderails and boards without openings
- Built-in bed exit detection system
- 2 or 3 levels of sensitivity
- Remote bed exit alarm connectivity
- Bed exit side view lights
- Smart screen on footboard control
- Trendelenburg angle displayed on footboard
- Auto-contour
- Programmable lowest height
- 3 position integrated bed extender :
80" / 203.2 cm 84" / 213.4 cm 90" / 228.6 cm
- One step vascular foot position
- Foot end back-up control on the frame
- CPR release handle
- Nightlights

Overall length (with bumpers)	88" / 224 cm
Extended length	92" - 98" / 234 - 249 cm
Overall width	
Siderails down	39.25" / 100 cm
Siderails up	40.5" / 102.9 cm
Weight capacity	40 stone / 272 kg
Height range (to litter top)	
Low	10" / 25.4 cm
High	30" / 76.2 cm
Patient surface positioning	
Backrest	0° to 60°
Knee Gatch	0° to 30°
Trend. / Reverse Trend.	± 16°
Patient surface dimensions	35" x 80" or 84" 88.9 x 203.2 or 213.4 cm
Caster diameter	5" / 12.7 cm
Bed weight	375 to 438 lb / 170 to 199 kg
Under bed clearance for hoist access	5" / 12.5cm
Compliant with standard	IEC 60601-1 3 rd edition 60601-2-52
Volts	120 V AC / 220-240 V AC
Ampere rating	4.25 A (9.25 A with 120 V outlets) / 2.15 A (4.15 A with 220 V outlets)
Current leakage	< 300 micro amps
Frequency	60 Hz / 50 Hz
Hospital grade plug	Yes
Battery type	Sealed rechargeable lead acid 1.2 Ah, 2 * 12 V