



Umanomedical

BARIATRIC & MED-SURG BED
POWERED WIDTH EXPANSION
481 KG CAPACITY

BED FEATURES

- 5 DC actuators
- Battery back-up
- 89 cm to 119.4 cm powered width adjustment
- 27.9 cm low height with 12.7 cm dual casters
- Programmable lowest height
- Programmable Auto-Contour mode
- Built-in bed exit detection system - 3 levels of sensitivity
- Remote bed exit alarm connectivity
- Smart screen, nurse controls and patient control lockout on footboard
- Nurse and patient controls integrated into siderails
- Trendelenburg angle displayed on footboard
- One hand release siderails
- 10 cm integrated bed extender
- CPR release handle
- Lifiable and flat deck covers
- One step Trendelenburg
- One step vascular foot position
- Integrated pump holder
- Boostless™ Backrest System
- Backrest angle indicator
- Nightlights
- Bed exit side view lights
- Communication port (for upgradable bed software)
- One-touch button groups
 - 30-degree head of bed
 - One-button chair position
 - Flat bed position
 - Backlit patient controls
 - Nurse call
- OIML Class 3 Scales

Specifications

ookSNOW»ALL

Product model	200-0000
Overall length (203 cm surface)	228.6 cm - 239 cm
Overall length (213 cm surface)	239 cm - 249 cm
Overall width	
Siderails down (89 cm surface)	101 cm
Siderails up (89 cm surface)	105.4 cm
Siderails down (119.4 surface)	130.8 cm
Siderails up (119.4 surface)	134 cm
Weight capacity	481 kg
Height range (to litter top)	
Low (12.7 cm dual casters)	27.94 cm
High (12.7 cm dual casters)	76.2 cm
Low (15.24 cm dual casters)	32.3 cm
High (15.24 cm dual casters)	80.5 cm
Patient surface positioning	
Backrest	0° to 60°
Knee gatch	0° to 30°
Trend. / Reverse Trend.	± 16°
Boostless™	12.7 cm
Patient surface dimensions	
Width	89 cm to 119.4 cm
Length	203 cm or 213 cm
Caster diameter	12.7 cm or 15.24 cm
Compliant with standard	IEC 60601-2-52
Certified for use by two people*	

*Two people refers to one patient and one companion.

Electronics

Compliant with standard	IEC 60601-1 3 rd edition
Volts	220-240 V AC
Ampere rating	2.15 A
Current leakage	< 300 micro amps
Frequency	60 Hz / 50 Hz
Battery type	Sealed rechargeable lead acid 1.2Ah, 2 * 12V

Umano Medical reserves the right to change specifications without notice.



International

01865 409926 • info@montcalmcare.co.uk